查询NTB23N03R供应商

NTB23N03R

Power MOSFET
23 Amps, 25 Volts
N−Channel D²PAK

Designed for low voltage, high speed switching applications in power supplies, converters and power motor controls and bridge circuits.

Features

- Pb−Free Packages are Available

Typical Applications

- Planar HD3e Process for Fast Switching Performance
- Low $R_{DS(on)}$ to Minimize Conduction Loss
- Low C_{iss} to Minimize Driver Loss
- Low Gate Charge
- Optimized for High Side Switching Requirements in High−Efficiency DC−DC Converters

MAXIMUM RATINGS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	25	Vdc
Gate−to−Source Voltage − Continuous	V_{GS}	±20	Vdc
Drain Current − Continuous @ T_A = 25°C, Limited by Chip − Continuous @ T_A = 25°C, Limited by Package − Single Pulse (t_p = 10 μs)	 I_D I_D I_{DM}	 23 6.0 60	A
Total Power Dissipation @ T_A = 25°C	P_D	37.5	W
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C
Thermal Resistance − Junction−to−Case	$R_{\theta JC}$	3.3	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 10 seconds	T_L	260	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

ON Semiconductor®

http://onsemi.com

23 AMPERES, 25 VOLTS
$R_{DS(on)}$ = 32 mΩ (Typ)

N−CHANNEL



MARKING DIAGRAM & PIN ASSIGNMENTS



D²PAK
CASE 418B
STYLE 2



T23N03 = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2005

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Characteristics		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage (Note 1) (V_{GS} = 0 Vdc, I_D = 250 μAdc) Temperature Coefficient (Positive)		$V(br)_{DSS}$	 25 −	 28 −	 − −	Vdc mV/°C
Zero Gate Voltage Drain Current (V_{DS} = 20 Vdc, V_{GS} = 0 Vdc) (V_{DS} = 20 Vdc, V_{GS} = 0 Vdc, T_J = 150°C)		I_{DSS}	 − −	 − −	 1.0 10	μAdc
Gate−Body Leakage Current (V_{GS} = ±20 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	−	−	±100	nAdc
ON CHARACTERISTICS (Note 1)						
Gate Threshold Voltage (Note 1) (V_{DS} = V_{GS}, I_D = 250 μAdc) Threshold Temperature Coefficient (Negative)		$V_{GS(th)}$	 1.0 −	 1.8 −	 2.0 −	Vdc mV/°C
Static Drain−to−Source On−Resistance (Note 1) (V_{GS} = 4.5 Vdc, I_D = 6 Adc) (V_{GS} = 10 Vdc, I_D = 6 Adc)		$R_{DS(on)}$	 − −	 50.3 32.3	 60 45	mΩ
Forward Transconductance (Note 1) (V_{DS} = 10 Vdc, I_D = 6 Adc)		g_{FS}	 −	 14	 −	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{DS} = 20 Vdc, V_{GS} = 0 V, f = 1 MHz)	C_{iss}	−	225	−	pF
Output Capacitance		C_{oss}	−	108	−	
Transfer Capacitance		C_{rss}	−	48	−	
SWITCHING CHARACTERISTICS (Note 2)						
Turn−On Delay Time	(V_{GS} = 10 Vdc, V_{DD} = 10 Vdc, I_D = 6 Adc, R_G = 3 Ω)	$t_{d(on)}$	−	2.0	−	ns
Rise Time		t_r	−	14.9	−	
Turn−Off Delay Time		$t_{d(off)}$	−	9.9	−	
Fall Time		t_f	−	2.0	−	
Gate Charge	(V_{GS} = 4.5 Vdc, I_D = 6 Adc, V_{DS} = 10 Vdc) (Note 1)	Q_T	−	3.76	−	nC
		Q_1	−	1.7	−	
		Q_2	−	1.6	−	
SOURCE−DRAIN DIODE CHARACTERISTICS						
Forward On−Voltage	(I_S = 6 Adc, V_{GS} = 0 Vdc) (Note 1) (I_S = 6 Adc, V_{GS} = 0 Vdc, T_J = 125°C)	V_{SD}	 − −	 0.87 0.74	 1.2 −	Vdc
Reverse Recovery Time	(I_S = 6 Adc, V_{GS} = 0 Vdc, dI_S/dt = 100 A/μs) (Note 1)	t_{rr}	−	8.7	−	ns
		t_a	−	5.2	−	
		t_b	−	3.5	−	
Reverse Recovery Stored Charge		Q_{RR}	−	0.003	−	μC

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
2. Switching characteristics are independent of operating junction temperatures.

ORDERING INFORMATION

Device	Package	Shipping†
NTB23N03R	D^2PAK	50 Units / Rail
NTB23N03RG	D^2PAK (Pb−Free)	50 Units / Rail
NTB23N03RT4	D^2PAK	800 Units / Tape & Reel
NTB23N03RT4G	D^2PAK (Pb−Free)	800 Units / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance versus Drain Current and Temperature



Figure 4. On−Resistance versus Drain Current and Temperature



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current versus Voltage



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage versus Total Charge



Figure 9. Resistive Switching Time Variation versus Gate Resistance



Figure 10. Diode Forward Voltage versus Current

PACKAGE DIMENSIONS

D²PAK
CASE 418AA−01
ISSUE O



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.036	0.51	0.92
E	0.045	0.055	1.14	1.40
F	0.310	−−−	7.87	−−−
G	0.100 BSC		2.54 BSC	
J	0.018	0.025	0.46	0.64
K	0.090	0.110	2.29	2.79
M	0.280	−−−	7.11	−−−
S	0.575	0.625	14.60	15.88
V	0.045	0.055	1.14	1.40

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN



VIEW W−W 1 | VIEW W−W 2 | VIEW W−W 3

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082−1312 USA
Phone: 480−829−7710 or 800−344−3860 Toll Free USA/Canada
Fax: 480−829−7709 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2−9−1 Kamimeguro, Meguro−ku, Tokyo, Japan 153−0051
Phone: 81−3−5773−3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.